## Amendments to the Claims:

Please cancel Claim 29 without prejudice or disclaimer. Please amend Claims 1 and 21 as follows. All pending claims are reproduced herein with a status identifier in parentheses after the claim number.

1. (Currently amended)

A floor tile comprising:

a flat, elongated base having a top surface, a bottom surface, a distal end and a proximal end, said base composed of a polymeric material and having a solid cross-section;

first and second opposite sides lying in respective first and second substantially parallel side planes;

a longitudinal axis disposed between and substantially parallel to said side planes; and

a plurality of longitudinally spaced, stepped edges formed on each of said distal and proximal ends of the base, each of the plurality of stepped edges formed by adjoining longitudinal and transverse edge portions, the longitudinal edge portion of one said edge lying in a longitudinal plane inward of one of said side planes and extending substantially parallel thereto and the transverse edge portion of the one said edge extending toward a base side to join a longitudinal edge portion of another one of said stepped edges.

2. (Original) The tile as claimed in Claim 1, wherein the longitudinal edge portions of the opposite ones of the stepped edges lie in the same longitudinal plane, whereby opposite stepped edges are in longitudinal alignment.

[10012877.1 ]

3. (Original) The tile as claimed in Claim 1, further comprising:

first and second interlock surfaces on said base extending substantially parallel to each of said first and second sides respectively for locking the tile to one or more similar adjacent tiles.

- 4. (Original) The tile as claimed in Claim 3, wherein the first and second interlock surfaces on the base face inward.
- 5. (Original) The tile as claimed in Claim 3, wherein each of said interlock surfaces comprises an Hermaphroditic interlock structure having first and second sidewalls spaced apart to form a partially enclosed, open-sided cavity facing outwardly from said base.
- 6. (Original) The tile as claimed in Claim 5, wherein the first interlock sidewall is the outermost sidewall, and wherein said sides of said base and said first sidewall form there between the male part of said interlock structure.

  Order as lumplified the male of first sidewall is the male of the said interlock structure.

7. (Original) The tile as claimed in Claim 5, wherein said first sidewall is inclined toward said first side with a slope of opposite polarity to that of the first sidewall adjacent said second side of said base.

[10012877.1]

- 8. (Original) The tile as claimed in Claim 1, further comprising an interlock surface formed in the base of said end inwardly of the edges of said step edges.
- 9. (Original) The tile as claimed in Claim 1, wherein the distal end of the base is formed by a first, second and third step.
- 10. (Original) The tile as claimed in Claim 9, wherein each step on the distal end of the base has a longitudinally aligned step on the proximal end of the base.
- 11. (Original) The tile as claimed in Claim 1, further comprising a plurality of said stepped edges on each of said distal and proximal ends of the base, thereby forming a stepped staircase arrangement, the staircase arrangement at one of said base ends being inverted with respect to the staircase arrangement at the opposite base end.
  - 12. (Original) The tile as claimed in Claim 11, wherein the steps of one of said staircase arrangements are longitudinally aligned with corresponding steps of an opposite staircase arrangement.
  - 13. (Original) The tile as claimed in Claim 1 or 2, further comprising:

    a decorative layer adhered to the top surface of the base.

(100)12877.1 }

14. (Original) The tile as claimed in Claim 13, wherein the base is formed by an injection molding process and wherein the decorative layer is a laminate molded to the base during the process.

Chint

15. (Original) The tile as claimed in Claim 1, further comprising, a wear-resistant layer adhered to the top surface of the base.

16. (Original) The tile as claimed in Claim 14, further comprising, a wear-resistant layer adhered to the decorative layer.

7

17. (Original) The tile according to Claim 13, wherein the base is at least partially composed of recycled plastic material.

18. (Original) The tile as claimed in Claim 13, wherein the decorative layer simulates the surface of a wooden floor, and additionally, wherein a plurality of longitudinally extending, parallel grooves are molded in said top surface to simulate a plurality of boards.

7

19. (Original) The tile as claimed in Claim 18, wherein each of said grooves is aligned with longitudinal edge portions of oppositely aligned step edges.

20. (Previously amended) The tile as claimed in Claim 1, wherein the step edges have longitudinal and transverse intersecting portions to simulate transverse staggering between individual boards of a wood floor.

B1 cl

21. (Currently amended) A floor tile assembly comprising:

a plurality of mutually adjacent tiles mechanically interlocked along the sides thereof for adhesive-free mounting to a surface,

wherein, each of said tiles comprises an elongated base of substantially solid rectangular cross-section of substantially equal width and having a longitudinal axis, a top and bottom surface and first and second substantially linear peripheral edges forming substantially straight borders, a pair of open-sided interlock structures molded in said base extending parallel to and adjacent to different ones of said first and second edges, the open side of the interlock structure adjacent the first side edge facing the bottom surface is disposed to engage a mating interlock structure of another adjacent tile from the top of said base, and a plurality of transverse stepped end surfaces, longitudinally spaced from one-another, formed on opposite ends of said base, whereby the base edges are staggered in the longitudinal direction.

22. (Original) The tile assembly according to Claim 21, further comprising:

a decorative layer adhering to said top surface of each tile simulating a section of a wood floor.

(10012877.1.)

ch:t

23. (Original) The tile assembly according to Claim 21, wherein the transversely stepped end surfaces on each tile are formed by a staircase of individual steps; each step having longitudinal and transverse intersecting portions to simulate transverse staggering between individual boards a wood floor.

US' tont

24. (Original) The tile assembly according to Claim 21, wherein the step staircases are positionally inverted relative to a central plane through a said base and perpendicular to said longitudinal axis, and wherein each step has a longitudinally disposed diagonal counterpart step on an opposite base end.

25. (Original) The tile assembly according to Claim 21, further comprising:

a plurality of top longitudinal grooves, each groove aligned with a longitudinal portion of a step and its opposite counterpart to simulate the longitudinally abutting edges of boards of a wood floor.

26. (Original) A floor tile molded of polymeric material, comprising:

a plurality of flat, elongated tile sections of substantially equal length and each of the plurality of tile sections having adjoining top surfaces of generally rectangular shape, said plurality of tile sections being joined in parallel longitudinally staggered relationship to simulate the staggering of abutting elongated boards in a wooden floor installation, a decorative layer on said top surface simulating a wood grain in each tile section, and matable interlock portion

don't

formed on the dges of said sections for mechanically interlocking the tile to similarly staggered tiles having matable interlock portions thereon.

27. (Original) A tile according to Claim 26, wherein each tile section is longitudinally spaced from its adjoining section of tile by substantially the same amount.

28. Canceled. (by Amdta)

29. Canceled